

The Leveler Kit is an supportive feature used to prevent tipping from occurring when stepping onto the trailer while off the hitch.

Parts List

Description	Qty
Leveler Jack	2
1/4 X 20 Bolt, 1 3/4"	4
1/4 - 8 Nylocks	4
1/4 USS Flat Washer	8
3/4" USS Flat Washer (Spacer)	2

Tools Needed

- Measuring Tape
- Marker
- Drill
- 9/32" Drill Bit
- 7/16" Wrench - 2



Assembly

The Leveler Jacks are attached with two 1/4 x 20 bolts through the C-Channel track inside the base of the trailer. The rear hole is pre-drilled through the plastic base. The front hole must be drilled. Use the hole in the C-Channel track as the pilot hole for drilling through the base.

Follow procedures outlined below. Note that the front bolt hole uses a large washer between the trailer base and the jack. This ensures clearance with the trailer's frame wing when the Leveler Jacks are retracted.

Front Bolt Hole:

Pre-drilled hole in C Channel Track. Use as pilot hole to drill through trailer base.

Rear Bolt Hole:

Remove bolt, attached jack, insert longer 1/4 x 20 bolt furnished

Front Bolt Hole, Underneath:

Sandwich washer between frame tube and jack



C-Channel Track



Leveler Assembly Kit

Operation

To extend legs, pull leg outwards to release the spring catch and detent lance. Allow the leg to swing downwards until the lance engages in the extended slot position.

To retract the legs, first minimize the leg length to the shortest position, then pull the leg downward to release the lance from its extended and locked position. Swing the leg upward into the retracted position until the lance catches in the retracted slot. Before driving, verify that the legs are retracted and that the locking lance is fully engaged in the locking slot.



1. To release from catch position, pull leveler forward (toward front of the trailer).



2. Swing Leveler down.



3. Adjust height by pressing downward on adjustment lever.

To prepare for transit, release adjustment lever to minimize leg length and fold upward to retract, caught position shown above.



WARNING

Always fold up Leveler Kit in secure position before operating trailer. To prevent damage, do not move trailer with stabilizers down.

For Assistance, contact Let's Go Aero at 877-464-2376 or 719-630-3800, or Support@LetsGoAero.com.

Visit our website at www.LetsGoAero.com

LET'S GO AERO
Gear Management Solutions