

Ease of Use Mobility System for GearSpace™ 34 and GearDeck™ 17 Cargo Carriers

- Roll on and roll off ease of use for your LGA cargo carrier.
- Legs nest underneath carrier in secure, reclined position for transit. Secure catch release mechanism allows for each leg to fold down or up.
- Height adjustable legs for varying vehicle hitch heights.
- Wheel feature allows for rolling away from vehicle to storage location.
- Designed for use on hard surfaces.



Four Models Available for Varying Weight Ratings and Leg Lengths:

Light Duty Models

Designed to aid the installation and removal of the GearDeck™ 17 and GearSpace™ 34 cargo carriers from the hitch when empty. Wheel support allows for rolling away from vehicle to place in storage area such as the garage.

- Kit consists of three (3) "E-coated" leg assemblies with 5" diameter wheel casters and heavy zinc coated hardware.
- Maximum weight rating: GearDeck™ 17 and GearSpace™ 34 carriers empty.

Part No. ACC 3280: Standard length model provides 16" carrier height for hitch installation and requires 11" minimum hitch height.

Part No. ACC 3281: Long length model provides 20" carrier height for hitch installation and requires 15" minimum hitch height.



Heavy Duty Models

Commercial grade designed for load bearing use of items such as portable generators, recreation gear, and luggage. Load bearing aid for the installation and removal of the GearDeck 17 and GearSpace™ 34 cargo carriers from the hitch. Wheel support allows for rolling away from vehicle to place in storage area such as the garage.

- Kit consists of four (4) "E-coated", bonded, leg assemblies with 5" diameter wheel casters and heavy zinc coated hardware.
- Maximum gross weight rating: 300 lbs.

Part No. ACC 3282: Standard length model provides 16" carrier height for hitch installation and requires 11" minimum hitch height.

Part No. ACC 3283: Long length model provides 20" carrier height for hitch installation and requires 15" minimum hitch height.

